

Order code: **MIMI13UNXXE01**

* When reordering spare transmitter/receiver, please, add the serial number of radiocontrol !



* Receiving Unit MITO MINI
9-30 Vac/dc with cableglad
output.
MRMIVUP9RXX01



MITO-BC 100-240 Vac Battery
Charger.
0401CA000121



90-264 Vac 5V 1.5A USB Pow-
er Supply.
0101AA000045

* Transmitting Unit MITO MINI
composed of 6 general single step
push buttons + Start and Stop.
MTMI13UNRXX01



Cable 1M USB-M A / DC Plug
90°
0101CG000035



Black plastic cover for Mito
Mini.
0405AT000104

TECHNICAL DATA

AT MITO MINI UN

Protection degree	IP67
Dimensions	60x113x26 mm
Weight	100 g

AR MITO MINI

Protection degree	IP67
Dimensions	107x165x50 mm
Weight	450 g

Working temperature	-25 ÷ +55 °C
Maximum voltage on contacts	230 Vac
Operating distance	150 m
ISM Working frequency	868,0125 ÷ 869,9875 MHz
Charged battery autonomy at 20 °C	~ 50 hours

Each system includes multilingual instruction manuals, CE certifications. Document subject to change, on elcaradio.biz the latest updated revisions.

Order code: MIMI13UNXXE01

* When reordering spare transmitter/receiver, please, add the serial number of radiocontrol !

COMMAND LAYOUT

