

Order code: **MIMIO4UNXXE02**

\* When reordering spare transmitter/receiver, please, add the serial number of radiocontrol !



\* Receiving Unit MITO MINI  
9-30 Vac/dc with cable gland  
output.  
**MRMIVUP9RXX01**



MITO-BC 100-240 Vac Battery  
Charger.  
**0401CA000121**



90-264 Vac 5V 1.5A USB Pow-  
er Supply.  
**0101AA000045**

\* Transmitting Unit MITO MINI  
composed of 8 general single step  
push buttons.  
**MTMIO4UNRXX01**



Cable 1M USB-M A / DC Plug  
90°  
**0101CG000035**



Black plastic cover for Mito  
Mini.  
**0405AT000104**

## TECHNICAL DATA

### AT MITO MINI UN

Protection degree	IP67
Dimensions	60x113x26 mm
Weight	100 g

### AR MITO MINI

Protection degree	IP67
Dimensions	107x165x50 mm
Weight	450 g

Working temperature	-25 ÷ +55 °C
Maximum voltage on contacts	230 Vac
Operating distance	150 m
ISM Working frequency	868,0125 ÷ 869,9875 MHz
Charged battery autonomy at 20 °C	~ 50 hours

Each system includes multilingual instruction manuals, CE certifications. Document subject to change, on elcaradio.biz the latest updated revisions.

Order code: **MIMI04UNXXE02**

\* When reordering spare transmitter/receiver, please, add the serial number of radiocontrol !

## COMMAND LAYOUT

